

# SECURE-ALL

## TDR IN FLOOR SAFES

**TORCH AND DRILL RESISTING**

● **LOCKING BY S&G 3 WHEEL  
1 MILLION CHANGE COMBINATION LOCK**

SIZE	HEIGHT	BASE		WEIGHT
<b>INTERNAL</b>	<b>265</b>	<b>280</b>	<b>280</b>	<b>DOOR 8KG</b>
<b>EXTERNAL</b>	<b>435</b>	<b>315</b>	<b>315</b>	<b>BODY 18KG</b>
<b>PRICE \$</b>				<b>TOTAL 28KG</b>
<b>INSTALLATION \$</b>				

**MODEL: SECA**

**MADE IN AUSTRALIA**

**SUGGESTED INSURABLE CASH RATING FOR SECURE-ALL FLOOR SAFES  
IN AN UNSUPPORTED (NO ALARMS) DOMESTIC SITUATION IS \$30,000**

**CMI**  
SAFE CO

**CMI SAFE CO.** A.C.N. 057 073 033

Head Office: 244 WEST STREET, CARLTON, N.S.W. 2218

Phone: (02) 9547 1488 (5 LINES) Fax: (02) 9547 2104

Web Site: [www.cmisafe.com.au](http://www.cmisafe.com.au) Email: [sales@cmisafe.com.au](mailto:sales@cmisafe.com.au)

Agents in all major cities throughout Australia.


**ASIAL**  
MEMBER AUSTRALIAN SECURITY  
INDUSTRY ASSOCIATION LIMITED

CD PONT 004 KB 1701



# SECURE-ALL

## TDR IN FLOOR SAFES



### TORCH AND DRILL RESISTING

- FLUSH FITTING LID TO AID CONCEALMENT AND FIRE PROTECTION
- INTERCHANGEABLE DOOR (8KG) SECURED BY 3 WHEEL S&G COMBINATION LOCK
- CLEAR 155mm ACCESS TO CONTENTS STORAGE AREA 265 x (280 x 280)

### RECOMMENDED INSTALLATION PROCEDURE.

The safes may be installed in either concrete or timber floors. The opening in the floor should be at least 500mm square by 550mm deep.

The safe should be secured with a strong mix concrete 1 x sand, 1 x stone, 1 x cement. Steel reinforcing material can also be used to help bond the concrete and provide better security.

It is recommended that the mix be poured so that a concrete cover of at least 100mm (4") exists around each side of the safe and brought level with top.

Floor safes are not waterproof. In damp situations the concrete should contain a waterproofing agent such as "Silasec" or "Yurite" (available from hardware stores). Whilst the concrete is setting, the door should be removed.

## MADE IN AUSTRALIA

**ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT & TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.**



**CMI SAFE CO.** A.C.N. 057 073 033

Head Office: 244 WEST STREET, CARLTON, N.S.W. 2218

Phone: (02) 9547 1488 (5 LINES) Fax: (02) 9547 2104

Web Site: [www.cmisafe.com.au](http://www.cmisafe.com.au) Email: [sales@cmisafe.com.au](mailto:sales@cmisafe.com.au)

Agents in all major cities throughout Australia.



CD PONT 004 KB 1701